



ENGINEERED FOR MOTION

NexGen Series Infrared Touchless Door Activator Switches



#NG-IR-A

Product Name

NexGen

Infrared Touchless Door Activator Switches

Contact Information

MS SEDCO
8701 Castle Park Drive
Indianapolis, IN 46256
Phone: (317) 842-2545
www.mssedco.com

Product Description

BASIC USE

The NexGen touchless switches are active infrared devices designed to activate full and low energy automatic doors.

Their touchless operation makes them ideal for ADA applications. Other applications include clean-room access points, request-to-exit devices (1 amp contact) and point-of-purchase displays. The NexGen Infrared Touchless switch is microprocessor controlled allowing for superior operation in a smaller unit.

Technical Data

- ADA Compliant Operation
- Faceplates Available in Various Finishes
- Microprocessor-Controlled Infrared Touchless
- Adjustable Reaction Time (0.05-3 Sec.)
- Digital Circuit Design
- 12 to 24V AC or DC Operation
- Form C Relay Output
- Heavy Duty 1 Amp Contact

Face Plate Finish

Standard: Brushed Stainless Steel
For Special Finishes Contact Factory

Temperature

-13°F to 140°F (-25°C to 60°C)

Recommended For Interior Use

APPLICABLE STANDARDS

American National Standards Institute (ANSI) - Building Hardware Manufacturers Association (BHMA) - ANSI/BHMA A156.10 & A156.19.

Installation

Refer to MS SEDCO Installation Instructions.

Availability & Cost

AVAILABILITY

Available internationally from manufacturer's authorized distributors; contact MS SEDCO for the location of the nearest distributor.

COST

Cost information on MS SEDCO products is available from the manufacturer's authorized distributors.

SPECIFICATIONS

Activation Method

NexGen technology using rapid infrared pulses, to ensure accurate detection.

Avg. Radiated Power

Less than 18mW

Input Voltage

12V to 24V AC or DC, not polarity sensitive

Input Current

Nominal $\pm 15\text{mA}$ @24V AC
Activated $\pm 40\text{mA}$ @ 24V AC

Relay Contacts

Form C rated at 1 amp @ 24V DC

Response Time/Reaction Time

Adjustable from 0.05 to 3 sec.

Operating Distance

$\pm 5"$ to 12"

Unit Size

4.5"W x 4.5"H x 0.75"D

Face Plate Sizes

Fits Single-gang or 2-gang Box
4 1/2"W x 4 1/2"H
Fits Single-Gang Box
2 3/4"W x 4 1/2"H

092015

NexGen Series Infrared Touchless Door Activator Switches



ENGINEERED FOR MOTION

Warranty

A one year warranty is available from the manufacturer covering defects in materials and workmanship. Contact MS SEDCO for details.

Maintenance

MS SEDCO recommends that all maintenance and adjustments be performed by an AAADM Certified Technician.

Technical Services

MS SEDCO's staff of factory trained sales and service personnel offer design assistance and technical support. Local distributors are also available to assist in selecting appropriate devices for specific uses and to provide onsite installation

DIMENSIONS

