

SIDE DOOR VAN RAMP Prairie View Industries, Inc.



- Easy installation
- Mounts to floor of van inside doorway
- Folds in quarters and stores vertically, leaving doorway accessible
- Patented center joint hinge eliminates pinch point and adds strength
- Durable welded construction
- Anti-slip, high traction surface
- Accommodates wheelchairs and scooters with various wheel configurations
- Not compatible with vans that have stow away seating

Listed by Underwriters Laboratories Inc.

NOTE: Minimum requirement for floor to ceiling opening: 6' ramp - 42", 7' ramp - 46"

LIMITED LIFETIME WARRANTY

Item Number	Length	Width	Folded Size	Weight	Capacity*
SDR626	6'	26"	38" x 13½" x 8¾"	32 lbs.	600 lbs.
SDR628	6'	28"	38" x 14½" x 8¾"	33 lbs.	600 lbs.
SDR728	7'	28"	44½" x 14½" x 8¾"	38 lbs.	600 lbs.

*Maximum ramp capacity: 300 lbs. (one axle) – 600 lbs. (two axles).

REAR DOOR VAN RAMP **LIMITED LIFETIME WARRANTY**



- Easy Installation**
- Mounts to floor of van inside doorway
- Three sections, manually operated with spring assist
- Easily operated by one person
- Stores vertically inside doorway
- Durable welded construction
- Anti-slip, high traction surface
- Accommodates wheelchairs and scooters with various wheel configurations
- Not compatible with vans that have stow away seating

Listed by Underwriters Laboratories Inc.

NOTE: Minimum inside door opening required for this ramp is 34". Minimum requirement for floor to ceiling opening: 7' ramp - 37", 8' ramp - 41".

Item Number	Length	Unfolded Size	Folded Height	Weight	Capacity*
VAN727	7'	7' X 27"	36"	72 lbs.	600 lbs.
VAN827	8'	8' X 27"	40"	77 lbs.	600 lbs.

* Maximum ramp capacity: 300 lbs. (one axle) – 600 lbs. (two axles).
 ** Conversion kit is required if rear door opening contains a threshold.

VAN RAMP ADAPTOR



- Reduces ramp slope and eases entry
- Lightweight, durable aluminum
- Anti-slip high traction surface
- Lightweight, Easy-to-handle and set up
- For use with Van Ramp models VAN727 and VAN827.

Item Number	Description	Size	Weight	Capacity*
VAN2426.75	One Piece	24" X 26¾"	8 lbs.	600 lbs.

* Maximum ramp capacity: 300 lbs. (one axle) – 600 lbs. (two axles).